










Developed specifically for the safe storage of platelets at the optimum temperature this Incubator features a keypad lock for security and a built in chart recorder. It has been designed to meet the BSQR standard for storing platelets and comply with MHRA regulations.

Like the rest of the Labcold Blood Product Storage range this incubator is a certified medical device in accordance with UK MDR 2002.







Simulated load alarm

This incubator has enough capacity to hold a Labcold flatbed Platelet Agitator (model number AGIT1006MD) with either a 6 or 8 tray rack which can be ordered separately.

When used with a Labcold Agitator the incubator features a motion sensor alarm to alert you of agitator failure and for extra safety the agitator will stop moving when the door is opened and only resume motion when the door is shut.

RLPI0130MD Platelet Incubator (Medical Device)

| Part Number | RLPI0130MD |
|---|--------------------------------------|
| Capacity (Litres) | 118 |
| Style | Freestanding |
| Exterior Dimensions (HxWxD) | 1045 x 655 x 670mm |
| Interior Dimensions (HxWxD) | 445 x 555 x 465mm |
| Energy Consumption | 1.3 kWh/24hr |
| Operating Temperature | +22°C +/- 2°C |
| Interior Construction | Stainless Steel |
| Exterior Construction | Powder Coated steel |
| Door Style | Glass |
| Door Hinging | Right |
| Open Door alarm | \checkmark |
| Load Temperature Alarm | \checkmark |
| Air Temperature Alarm | \checkmark |
| Mains Failure Alarm | ✓ |
| Motion Failure Alarm | √ |
| Air Temperature Display | √ |
| Load Temperature Display | ✓ |
| 7 Day Chart Recorder | √ |
| Lock | Digital Keypad |
| Battery Back up (Display) | √ |
| Microprocessor Control | √ |
| Remote alarm contacts | √ |
| Access Port | √ |
| Auto Defrost | Х |
| Internal Light | √ |
| Warranty | 2 year parts and labour (UK only) |
| Eco Friendly Refrigerant | √ |
| Certified Medical Device in Accordance with Directive UK MDR 2002 | √ |



