









The Labcold Breast Milk refrigerator has been specifically designed to store human milk in optimum conditions. With three adjustable shelves and an interior fan for even temperature distribution, this fridge is fitted with a lock for extra security.



The flat touch screen controller displays the internal temperature of the fridge, but it also shows minimum and maximum temperatures which can be displayed at the touch of a button. It also alarms if the internal temperature drops below 0°C or rises above 5°C. The Breast Milk fridge is also fitted with a door open alarm and, if batteries are fitted, a mains failure alarm.

There is also a second temperature probe which can be placed where ever you see fit. The controller will also display the temperature of that probe and alarm when it detects high or low temperatures plus record min/max readings.



The RLBM1019 comes complete with a door handle designed to stand proud of surrounding units for easy opening and closing.

We are confident that this breast milk refrigerator will provide you with many years of fault free service. However, for extra peace of mind your RLBM1019 comes complete with a FREE 1 year parts and labour warranty!*

The IntelliCold® controller automatically stores temperature data for both probes and refrigerator performance. A specifically encoded Micro SD card is available as an optional extra for data transfer so these records can be stored to your PC. Why not ask for details when you place your order?



RLBM1019 Breast Milk Refrigerator

Part Number	RLBM1019
Capacity (Litres)	150
Style	Free Standing
Exterior Dimensions (HxWxD)	1510 x 600 x 700mm
Interior Dimensions (HxWxD)	1358 x 480 x 500mm
Temperature Range	0°C to 5°C
Operating Temperature	+3°C
Interior Construction	Powder Coated Steel
Exterior Construction	Powder Coated Steel
Shelves	6
Adjustable Feet	✓
Automatic Temperature & Fridge Operation Data Recording	✓
Door Style	Solid
Door Hinging	Right (can be reversed at time of manufacture)
Door Lock	✓
Self Closing Door	✓
Digital Temperature Control	✓
Digital Temperature Display	✓
Internal Light	✓
High/Low Temperature Alarm	
_ Minimum/Maximum	✓
Temperature Recording	√ √
Temperature Recording Door Open Alarm	√ √
	√ √ √
Door Open Alarm	√ √
Door Open Alarm Mains Failure Alarm	√ √
Door Open Alarm Mains Failure Alarm Alarm Battery Back-Up	√ √ √
Door Open Alarm Mains Failure Alarm Alarm Battery Back-Up Off cycle auto defrost	√ √ √
Door Open Alarm Mains Failure Alarm Alarm Battery Back-Up Off cycle auto defrost Second Temperature Probe	√
Door Open Alarm Mains Failure Alarm Alarm Battery Back-Up Off cycle auto defrost Second Temperature Probe Fan Assisted Cooling	√
(HxWxD) Temperature Range Operating Temperature Interior Construction Exterior Construction Shelves	0°C to 5°C +3°C Powder Coated Steel Powder Coated Steel 6





